

# MI-490DS-A1

## 49" Digital Signage Touch Monitor




### Description

The new MI-490DS-A1 49" interactive touch monitor is a newly designed solution for a variety of applications. Engineered with an improved airgap between the sensor and LCD, improving optical clarity, protection against dust and moisture build-up over time, while increasing touch accuracy. The MI-490DS-A1 features a premier anti-glare finish, driving better light dispersion and viewing performance in high ambient light applications. Supporting more than 40 touch points, multiple styli and erasers, this display is a drop-in solution for not only retail/hospitality signage and wayfinding, but collaboration applications as well. Combining the ultra-slim design, enhanced anti-glare finish, the versatile I/O selection, peak optical performance with 4k resolution, this display is a solution that can exceed a wide range of application requirements.

### Featured Specifications

- Size: 49" TFT LCD
- Maximum Resolution: 3840 x 2160
- Contrast Ratio: 1100:1
- Aspect Ratio: 16:9
- Brightness: 500 nits (No Touch), 450 nits (P-CAP)
- View Angle: H: 178°, V: 178°
- Video Port: 2 x HDMI/1 x DisplayPort/1 x VGA
- Warranty: 3 year



# Specifications

## Touch LCD Display

Touch Screen	Projected Capacitive
Touch Points	>40 (with stylus support)
Touch Screen Interface	USB-HID (Type B)
Surface Treatment	Anti-Glare

## I/O Ports

Serial Port	1 x RS232 (DB9)
USB Port	2 x USB Type B (touch) 1 x USB 2.0 Type A
Video Port	2 x HDMI / 1 x DisplayPort / 1 x VGA
Audio Port	PC Audio in/out, SPDIF out
Power Input	AC Input 100~240Vac, 50~60Hz
Power Output	AC output IEC C13 type

## Physical Properties

Power Supply	Max: 150W
Speaker	10W x 2
Orientation	Portrait/Landscape/Tabletop
Housing Color	Black
Construction	Glass, SECC Metal
Compliance	IP65 – Front only
Dimensions (W x H x D) mm	1127.6 x 657.8 x 78.8 mm
Net Weight (kg)	33.7 kg
Gross Weight (kg)	35.3 kg
Carton (W x H x D) mm	1274 x 227 x 824 mm
VESA	300 x 300 mm
Ball Drop	IK06

## Safety

Certifications	FCC/CE/UL/NOM/CEC/UKCA
----------------	------------------------

## Environment

Operating Temperature	0°C ~ 40°C, 35% ~ 85%, RH. Non-Condensing
Storage Temperature	-20°C ~ 60°C, 35% ~ 85% RH. Non-Condensing



[www.MicroTouch.com](http://www.MicroTouch.com) | [us.orders@microtouch.com](mailto:us.orders@microtouch.com)

TES America, LLC | 215 Central Avenue, Holland, MI 49423 | (616) 786-5353

The information presented in this specification sheet is intended as general information about MicroTouch products and is subject to change. Product specifications and warranties will be governed by TES America, LLC. standard terms and conditions of sale. Products are subject to availability. Copyright © 2022 TES America, LLC. All rights reserved. MT22-1100