

Clarity 23.8" ED Open Frame Display

The Clarity Touch and Display range has been developed to provide manufacturers with maximum product flexibility combined with minimum integration cost.

The range features a standard frame design that can be upgraded to incorporate:

- [MicroTouch Single-Touch SCT System](#)
- [MicroTouch Multi-Touch PCAP System](#)
- [ThruTouch](#)
- [MicroTouch Protective Glass \(SCT / PCAP Options\)](#)

The rugged metal frame provides integration points on all 4 back sides and a VESA mount to the back. The screens come equipped with industrial electronics and TFT panels for maximum reliability and performance. The AD board supports standard 3 point connection for VGA/DVI and DP (Display Port) and offers standard 12 volt operation.



FEATURES

- Wide Viewing Angle Display
- VGA / DVI / DP Signal input
- USB B Touch Output
- 100mm VESA Mount to Back
- Mounting Points all 4 Sides
- Option on for Touch
- Standard 12 Volt Operation

TECHNICAL SPECIFICATION (DISPLAY ONLY)

Resolution	1920 x 1080
Inputs	VGA / DVI / DP (1.2)
Operating Temperature	0°C to 50°C
Luminance	250cd/m2
Contrast Ratio	1000:1
Active Display Area	527.04 (W) x 296.46 (H)
Outer Dimensions	545.4 (W) x 323.9 (H) x 49.2 (D)

DESCRIPTION	PART NO.	ACCESSORIES	PART NO.
23.8" ED Open Frame Display	31161353	VGA Cable 1.8m	31123929
23.8" ED + MicroTouch Single-Touch SCT System	31161023	DVI Cable 1.8m	31123920
23.8" ED + SCT Style Protective Glass	31161024	DP Cable 1.5m	31123943
23.8" ED MicroTouch Multi-Touch PCAP System	31161334	USB Cable A/B 1.8m	31130143
23.8" ED + PCT Style Protective Glass	31161335	PSU 12V 3.5A	31145342
23.8" ED + ThruTouch	31161044S	UK Power Cord 1.8m	13021102
		EU Power Cord 1.8m	33145324