

Clarity 27" ED Open Frame Display

The Clarity Touch and Display range has been developed to provide manufacturers with maximum product flexibility combined with minimum integration cost.

The range features a standard frame design that can be upgraded to incorporate:

- MicroTouch Multi-Touch PCAP System
- MicroTouch Glass

The screens come equipped with industrial electronics and TFT panels for maximum reliability and performance. The AD board supports standard 3 point connection for VGA/ DVI and DP (Display port) and offers standard 12 volt operation.



Features

- Wide Viewing Angle Display
- VGA / DVI / DP Signal input
- USB B Touch Output
- Mounting Points to back of frame
- Option for Touch/Protective Glass
- Standard 12 Volt Operation

Technical Spec – Display only

- Resolution 1920 x 1080
- Inputs VGA / DVI / DP (1.2)
- Operating Temperature 0°C to 50 °C
- Luminance 300cd/m²
- Contrast Ratio 3000:1
- Active Display Area 597.6 (W) x 336.15 (H)
- Outer Dimensions 616 (W) x 364.6 (H) x 37.3 (D)

Description	Part No.	Accessories	Part No.
27" ED AUO Open Frame Display	31161096	VGA Cable 1.8m	31123929
27" ED AUO + MicroTouch PCAP Touch	31161097	DVI Cable 1.8m	31123920
27" ED AUO + MicroTouch Glass	31161098	DP Cable 1.5m	31123943
		USB Cable A/B 1.8m	31130143
		PSU 12v 3.5 amp	33145342
		UK Power Cord 1.8m	13021102
		EU Power Cord 1.8m	33145324